

CUTTY

SINGLE-PLY CUTTER COMPACT, FAST AND RELIABLE









The "Cutty" single-ply cutter series from Kuris is the fourth generation of the proven cutters which has been completely overhauled and optimised. It is noted for the individually optimised cutting head with a programmable Z-axis. The machines are all designed for maximum productivity and optimum production quality. The tool technology can be adapted individually and precisely to the respective

material. This means that optimum cutting conditions are always achieved. The fourth generation is equipped with Multiflex tool adaptation. As well as offering extremely short plunge times, this system also offers a persuasive choice thanks to the fast positioning and cutting speeds. In addition, the tool-change system reduces the set-up times considerably because fewer adjustment operations are required.

The cutter achieves positioning speeds of up to 100 metres per minute and, depending on the type of material, the cutting speed is up to 70 metres per minute. The machine is optionally available with a 7.5 or 11 KW vacuum pump. The standard user interface and menu navigation ensures that the machine operator can quickly get to grips with the machine across a range of technologies. Operating errors and the cost of training are drastically reduced. Even at high speeds, the machine cuts consistently and reliably. The mobile and innovative control system is very user-friendly.



Optionally with double bridge: Two bridges for independent cutting with two cutting heads in one cut pattern.

Cutting time saving: up to 40%






TECHNICAL DATA

Max. cutting height:	40 mm (depending on tool)
Max. cutting speed:	70 m/min
Max. positioning speed:	100 m/min
Max. acceleration:	7 m/s²
Nominal working widths (Y):	1.75 m / 2.15 m / 2.75 m
Table widths:	2.30 m / 2.70 m / 3.30 m (more on request)
Nominal working lengths (X):	2.30 m / 3.50 m
Total lengths:	
Weight of the cutter:	1950 kg / 2300 kg / 3800 kg
Working height:	from 0.85 m

Operating voltage:	400 V, 50/60 Hz
Connected electrical load	
Control / drives:	4 kW
Vacuum unit:	7.5 kW / 11 kW / 18 kW
Average consumption:	8 kW
Fuse:	35 A (5x6mm²)
Protection class:	Class 1
Compressed air (5-6 bar):	10 l/min



Options:

- Drawing device
- Drilling device
- Milling device
- Drag knife
- Driven round knife
- Oscillating knife (electrically powered)
- POT knife (pneumatically powered)
- Printhead

Noise level: 57 - 74 dB(A)

Mark of conformity: CE



Short set-up times thanks to plug & cut connection





Cleaning brush: This optionally available cleaning unit eliminates any cutting residues

The comprehensive product range also allows solutions tailored to your particular needs. In our showroom, spreading and cutting machines are available for general demonstrations as well as for test cuts with your own materials.

Arrange an appointment with us.
We will be delighted to advise you!



DEMONSTRATION VIDEO

Scan QR-code or visit www.kuris.de/video/cutty

Kuris Spezialmaschinen GmbH

Degginger Straße 6

Technical changes maybe possible.

D-73326 Deggingen - Reichenbach

Fon: +49 (0) 73 34 - 9 24 80 - 0 Fax: +49 (0) 73 34 - 9 24 80 - 69

E-Mail: info@kuris.de